

# Subway Tile

GLAZED CERAMIC

BEST TILE® / BESTTILE.COM

# Chatham

## COLORS, SIZES & AVAILABILITY

NOMINAL SIZE	FINISH	THICKNESS	GROUT JOINT	WHITE
3 x 6	Glossy	9 mm	3/16"	✓
3 x 6	Matte	9 mm	3/16"	✓
2.5 x 10	Glossy	9 mm	3/16"	✓
2.5 x 10	Matte	9 mm	3/16"	✓
4 x 16	Glossy	9 mm	3/16"	✓
4 x 16	Matte	9 mm	3/16"	✓
4 x 8 Elongated Hex	Glossy	9 mm	3/16"	✓
4 x 8 Elongated Hex	Matte	9 mm	3/16"	✓
.5 x 12 Jolly Trim	Glossy	9 mm	3/16"	✓
.5 x 12 Jolly Trim	Matte	9 mm	3/16"	✓

✓ Stock Item. ⚠ Non-Stock Item. Requires Extra Lead Time.

## TECH INFO

R = Residential, LC = Light Commercial, C = Commercial

<b>ORIGIN:</b> Spain <b>SHADE VARIATION:</b> V1 - Uniform Appearance <b>WEAR RATING:</b> 1 - Wall Applications Only	RECOMMENDED APPLICATIONS	R	LC	C
	FLOORS			
	WALLS / BACKSPLASH	●	●	●
	POOL DECKING			
	EXTERNAL USE - FROST PROOF			

● Approved for this application. \* Discuss proper installation method with your Sales Representative.

## TILE PERFORMANCE DATA

TECHNICAL FEATURE	NORMS	RESULTS
Water Absorption	ISO 10545-3	> 10 %
Abrasion Resistance (Glazed)	ISO 10545-7	1
Breaking Strength	ISO 10545-4	> 600 N
Dimensions Range	ISO 10545-2	Conforms
Chemical Resistance - Household Chemicals	ISO 10545-13	GHA/GLA
Chemical Resistance - Low Concentration of Acids and Bases	ISO 10545-13	GHA/GLA
Resistance to Stains	ISO 10545-14	Min Class 3
Crazing Resistance of Glazed Tiles	ISO 10545-11	Resistant

Always inspect materials prior to installation. Always mix 2-3 cartons at a time while installing to ensure the best blend. All product images are representative only. Variation in color and shading is to be expected. Final selection should be made from actual tile samples.