

Wood Look

COLOR BODY • GLAZED PORCELAIN

BEST TILE® / BESTTILE.COM

Tapestry Wood

COLORS, SIZES & AVAILABILITY

NOMINAL SIZE	FINISH	THICKNESS	GROUT JOINT	ICE	MALT	MOKA	SMOKE	COLORS
				✓	✓	✓	✓	✓
8 x 48 Rectified	Matte	9.5 mm	1/8"	✓	✓	✓	✓	
8 x 8 Lis	Matte	8.7 mm	3/16"			✓	✓	
8 x 8 Parq	Matte	8.7 mm	3/16"			✓	✓	
8 x 8 Flor	Matte	8.7 mm	3/16"			✓	✓	✓
8 x 8 Medi	Matte	8.7 mm	3/16"			✓	✓	

✓ Stock Item. ◊ Non-Stock Item. Requires Extra Lead Time.

TECH INFO

R = Residential, LC = Light Commercial, C = Commercial

ORIGIN: Spain SHADE VARIATION: V3 - Moderate Variation WEAR RATING: 8x48: 5 - Walls + Residential / Commercial Floor Applications; 8x8 Colors: 4 - Walls + Residential / Light Commercial Floor Applications; 8x8 Moka & Smoke: 3 - Walls + Residential Floor Applications It is not recommended to stagger any tile longer than 15" more than 1/3 the length of the tile.	RECOMMENDED APPLICATIONS	R	LC	C
	FLOORS	●	✦	✦
	WALLS / BACKSPLASH	●	●	●
	POOL DECKING	*	*	
	EXTERNAL USE - FROST PROOF	*	*	


● Approved for this application. ✦ 8x8 Colors approved for LC; 8x48 approved for C. * Discuss proper installation method with your Sales Representative.

TILE PERFORMANCE DATA

TECHNICAL FEATURE	NORMS	RESULTS
Water Absorption	ISO 10545-3	≤ 0.5 %
Deep Abrasion	ISO 10545-6	<130 mm ³ (8x48)
Abrasion Resistance (Glazed)	ISO 10545-7	3 / 4 / 5
Breaking Strength	ISO 10545-4	≥ 52 N/mm ² (8x48); ≥ 46 N/mm ² (8x8)
Dynamic Coefficient of Friction Wet	Acu Test	≥ 0.60
Frost Resistance	ISO 10545-12	Frost Proof
Chemical Resistance - Household Chemicals	ISO 10545-13	A/LA/HA
Chemical Resistance - Low Concentration of Acids and Bases	ISO 10545-13	A/LA/HA
Resistance to Stains	ISO 10545-14	Class 5



Lis - Smoke (SMOKE/ICE)



Parq - Smoke (SMOKE/ICE)



Flor - Colors (MULTI)



Medi - Moka (MOKA/MALT)

Always inspect materials prior to installation. Always mix 2-3 cartons at a time while installing to ensure the best blend. All product images are representative only. Variation in color and shading is to be expected. Final selection should be made from actual tile samples.