

Brick Look

GLAZED PORCELAIN

BEST TILE® / BESTTILE.COM

Tuscan Brick

COLORS, SIZES & AVAILABILITY

NOMINAL SIZE	FINISH	THICKNESS	GROUT JOINT	BLUE	RUST	COTTO	GREIGE	WHITE
3 x 10	Matte	8 mm	3/16"	✓	✓	✓	✓	✓

✓ Stock Item. ⚠ Non-Stock Item. Requires Extra Lead Time.

TECH INFO

R = Residential, LC = Light Commercial, C = Commercial

ORIGIN: Portugal SHADE VARIATION: V3 - Moderate Variation WEAR RATING: White: Class 5 - Rated for all residential and commercial applications; Greige / Blue: Class 4 - Rated for all residential and light commercial applications; Rust / Cotto: Class 2 - Rated for light residential applications	RECOMMENDED APPLICATIONS	R	LC	C
	FLOORS	●	✦	✦
	WALLS / BACKSPLASH	●	●	●
	POOL DECKING	*		
	EXTERNAL USE - FROST PROOF	*	*	

● Approved for this application. ✦ Greige & Blue approved for LC; White approved for C. * Discuss proper installation method with your Sales Representative.

TILE PERFORMANCE DATA

TECHNICAL FEATURE	NORMS	RESULTS
Water Absorption	ASTM C373	≤ 0.2 %
Abrasion Resistance (Glazed)	ASTM C1027	2 / 4 / 5
Dynamic Coefficient of Friction Wet	AcuTest	≥ 0.42
Thickness Dimension	ASTM C499	In accordance
Facial Dimension	ASTM C499	In accordance
Warping Diagonal	ASTM C485	In accordance
Wedging	ASTM C502	In accordance
Frost Resistance	ASTM C1026	Frost Proof
Chemical Resistance	ASTM C650	GL: GA, GLA

Always inspect materials prior to installation. Always mix 2-3 cartons at a time while installing to insure the best blend. All product images are representative only. Variation in color and shading is to be expected. Final selection should be made from actual tile samples.