

# Subway Tile

GLAZED CERAMIC

BEST TILE® / BESTTILE.COM

# Best White

## COLORS, SIZES & AVAILABILITY

NOMINAL SIZE	FINISH	THICKNESS	GROUT JOINT	WHITE
3 x 6	Glossy	7.7 mm	3/32"	✓
3 x 6	Matte	7.7 mm	3/32"	✓
3 x 6 Bullnose	Glossy	7.7 mm	3/32"	✓
3 x 6 Bullnose	Matte	7.7 mm	3/32"	✓

✓ Stock Item. ⌚ Non-Stock Item. Requires Extra Lead Time.

## TECH INFO

R = Residential, LC = Light Commercial, C = Commercial

<b>ORIGIN:</b> Brazil	<b>RECOMMENDED APPLICATIONS</b> R    LC    C	FLOORS	●    ●    ●	●    ●    ●
<b>SHADE VARIATION:</b> V1 - Uniform Appearance				
<b>WEAR RATING:</b> 1 - Wall Applications Only				
		EXTERNAL USE - FROST PROOF		

● Approved for this application. \* Discuss proper installation method with your Sales Representative.

## TILE PERFORMANCE DATA

TECHNICAL FEATURE	NORMS	RESULTS
Water Absorption	ISO 10545-3	10-20 %
Abrasion Resistance (Glazed)	ISO 10545-7	1
Breaking Strength	ISO 10545-4	≥ 125 lbf
Chemical Resistance - Household Chemicals	ISO 10545-13	Class E
Resistance to Stains	ISO 10545-14	Class A

Always inspect materials prior to installation. Always mix 2-3 cartons at a time while installing to ensure the best blend. All product images are representative only. Variation in color and shading is to be expected. Final selection should be made from actual tile samples.