

Fabric Look

GLAZED CERAMIC

BEST TILE® / BESTTILE.COM

Tapestry

COLORS, SIZES & AVAILABILITY

NOMINAL SIZE	FINISH	THICKNESS	GROUT JOINT	AZUL	BLANCO	MARFIL	OCEAN	PERLA	SALVIA	TERRACOTTA	VISON
4 x 16	Matte	9.3 mm	3/16"	✓	✓	✓	✓	✓	✓	✓	✓
12 x 36 Rectified	Matte	10.6 mm	1/8"	✓	✓	✓					✓
12 x 36 Art Rectified	Matte	10.6 mm	1/8"	✓						↻	✓

✓ Stock Item. ↻ Non-Stock Item. Requires Extra Lead Time.

TECH INFO

ORIGIN: Spain SHADE VARIATION: V3 - Moderate Variation WEAR RATING: 1 - Wall Applications Only It is not recommended to stagger any tile longer than 15" more than 1/3 the length of the tile.	RECOMMENDED APPLICATIONS	R	LC	C
	FLOORS			
	WALLS / BACKSPLASH	●	●	●
	POOL DECKING			
	EXTERNAL USE - FROST PROOF			

● - Approved for this application. * - Discuss proper installation method with your Sales Representative.

TILE PERFORMANCE DATA

TECHNICAL FEATURE	NORMS	RESULTS
Water Absorption	ISO 10545-3	> 10%
Abrasion Resistance (Glazed)	ISO 10545-7	1
Breaking Strength	ISO 10545-4	≥ 13 N/mm ² (4"x16"); ≥ 19 N/mm ² (12"x36")
Chemical Resistance - Household Chemicals	ISO 10545-13	A/LA/HA
Chemical Resistance - Low Concentration of Acids and Bases	ISO 10545-13	A/LA/HA
Resistance to Stains	ISO 10545-14	Class 5 (4"x16"); Class 3 (12"x36")

Always inspect materials prior to installation. Always mix 2-3 cartons at a time while installing to ensure the best blend. All product images are representative only. Variation in color and shading is to be expected. Final selection should be made from actual tile samples.