



AVAILABLE SIZES

12x24

3 x 24 Bullnose

DESCRIPTION

Make a statement. Ignite energy. An electrifying design sparks the imagination in our newest porcelain tile offering. Imported from Italy, this high quality tile evokes a dynamic edge with its brilliant combination of iridescent glazes and shimmering brush strokes. Flair.7 is available in seven vibrant shades; red, blue, ivory, beige, grey, brown and black. A spontaneous splash of color is sure to accentuate the focal point of any design. Sizes include 12x24 and 3x24 bullnose.

COLORS















TECHNICAL INFORMATION

TILE SIZES

Nominal	Shape	Finish	Thickness
12 x 24		Texture - Matte	10 mm

COORDINATING TRIM

Nominal	Shape	Finish	Thickness
3 x 24 Bullnose		Texture - Matte	10 mm

PERFORMANCE DATA

CHARACTERISTIC	NORMS	RESULTS
Water Absorption	ISO 10545-3	0.05%
PEI Abrasion Resistance (Glazed)	ISO 10545-7	5
Breaking Strength	ISO 10545-4	≥ 35 N/mm2
Static Coefficient of Friction Wet	C1028	≥ 0.60
Dimensions Range	ISO 10545-2	Conforms
Frost Resistance	ISO 10545-12	Frost Proof
Chemical Resistance - Household Chemicals	ISO 10545-13	Resistant
Thermal Shock Resistance	ISO 10545-9	Resistant
Resistance to Stains	ISO 10545-14	Cleanable

RECYCLED CONTENT



Intense and Elegance each contain 20% Pre-Consumer Recycled Content.

SHADE VARIATION



V2 - SLIGHT VARIATION

Clearly distinguishable differences in texture and/or pattern within similar colors.

WEAR CODE

5 - Rated for all residential and commercial applications.

APPLICATIONS

	RESIDENTIAL	LIGHT COMMERCIAL	COMMERCIAL
FLOORS	×	×	×
WALLS / BACKSPLASH	×	×	×
POOL DECKING	*	*	*
EXTERNAL USE - FROST PROOF	×	*	*

 $[\]boldsymbol{\varkappa}$ - Has been approved for this application.

<u>NOTES</u>

It is not recommended to stagger any tile longer than 18" more than 1/3 the length of the tile.

Always inspect materials prior to installation.

Always mix 2-3 cartons at a time while installing to insure the best blend.

^{* -} Information is available upon request.