

World Slate | Glazed Porcelain



AVAILABLE SIZES

3.125x6.5

6.5x6.5

13x13

2x2 Mosaic

6.5x20

20x20


3.125x13 Bullnose

DESCRIPTION


Indistinguishable from natural slate, with the texture of clefing and varied surfaces...all on an Italian glazed porcelain. We use highly advanced printing technology to give the unmistakable look and touch of natural slate. Come into one of our showrooms to see and feel for yourself.

COLORS




cream



mist









taupe




TECHNICAL INFORMATION

TILE SIZES

Nominal	Shape	Finish	Thickness
3.125 x 6.5		Matte	10 mm
6.5 x 6.5		Matte	10 mm
13 x 13		Matte	10 mm
2 x 2 Mosaic		Matte	10 mm
6.5 x 20		Matte	10 mm
20 x 20		Matte	10 mm

COORDINATING TRIM

Nominal	Shape	Finish	Thickness
3.125 x 13 Bullnose		Matte	10 mm

PERFORMANCE DATA

CHARACTERISTIC	NORMS	RESULTS
Water Absorption	ISO 10545-3	≤ 0.4 %
PEI Abrasion Resistance (Glazed)	ISO 10545-7	5
Breaking Strength	ISO 10545-4	40-55 N/mm ²
Static Coefficient of Friction Wet	C1028	0.61
Frost Resistance	ISO 10545-12	Frost Proof
Chemical Resistance - Household Chemicals	ISO 10545-13	Resists
Chemical Resistance - Low Concentration of Acids and Bases	ISO 10545-13	Resists
Scratch Hardness	MOHS	6
Resistance to Stains	ISO 10545-14	Complete

SHADE VARIATION



V3 - MODERATE VARIATION

While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece may vary significantly. For example "that little bit of color" on one piece of tile may be the primary color on the next piece.

WEAR CODE

Mist / Taupe: 4 - Rated for all residential and light commercial applications.

Cream: 5 - Rated for all residential and commercial applications.

APPLICATIONS

	RESIDENTIAL	LIGHT COMMERCIAL	COMMERCIAL
FLOORS	×	×	Cream
WALLS / BACKSPLASH	×	×	×
POOL DECKING	*	*	
EXTERNAL USE - FROST PROOF	×	*	

× - Has been approved for this application.

* - Information is available upon request.

NOTES

It is not recommended to stagger any tile longer than 18" more than 1/3 the length of the tile.

Always inspect materials prior to installation.

Always mix 2-3 cartons at a time while installing to insure the best blend.