



# Balmwood | Ceramic

## AVAILABLE SIZES



## DESCRIPTION

A ceramic tile that offers a wood tile look. Balmwood is a high-quality Spanish ceramic floor tile with a soft wood look elevated by a sophisticated sheen that brightens any floor tile installation. Four colors comprise this value-priced collection.

## COLORS

beige



teka



wengue




gris



# TECHNICAL INFORMATION

## TILE SIZES

Nominal	Shape	Finish
6 x 24		Matte

## PERFORMANCE DATA

CHARACTERISTIC	NORMS	RESULTS
Water Absorption	ISO 10545-3	3% <value< 6%
Abrasion Resistance (Glazed)	ISO 10545-7	Wengue - 3 All Others - 4
Breaking Strength	ISO 10545-4	Min 1000 N
Dynamic Coefficient of Friction Wet	AcuTest	0.29
Dimensions Range	ISO 10545-2	Conforms
Frost Resistance	ISO 10545-12	No
Chemical Resistance - Household Chemicals	ISO 10545-13	GLA/GHA
Thermal Shock Resistance	ISO 10545-9	Passes Test
Resistance to Stains	ISO 10545-14	Class 5

## SHADE VARIATION



### V3 - MODERATE VARIATION

While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece may vary significantly. For example "that little bit of color" on one piece of tile may be the primary color on the next piece.

## WEAR CODE

Wengue: 3 - Rated for all residential applications.

All Others: 4 - Rated for all residential and light commercial applications.

## APPLICATIONS

	RESIDENTIAL	LIGHT COMMERCIAL	COMMERCIAL
FLOORS	X	X (all except Wengue)	
WALLS / BACKSPLASH	X	X	
POOL DECKING			
EXTERNAL USE - FROST PROOF			

X - Has been approved for this application.

\* - Information is available upon request.

## NOTES

It is not recommended to stagger any tile longer than 18" more than 1/3 the length of the tile.

Minimum Grout Joint Recommendation: 3/16"

Always inspect materials prior to installation.

Always mix 2-3 cartons at a time while installing to insure the best blend.

All product images are representative only. Variation in color and shading is to be expected. Final selection should be made from actual tile samples.