






Colorful | Porcelain












AVAILABLE SIZES



DESCRIPTION







Colorful porcelain tile offers exactly what it means: a collection of floor tile and wall tile in which blue tiles, green tiles, light grey and dark grey tiles, along with classic black and white tiles are all showcased in this upscale, Italian porcelain tile series in both a matte finish and glossy finish. Available in both square tile or rectangular tile shapes, Colorful is the perfect option for classic looks or unique one-of-a-kind color combinations.

COLOR / SIZE AVAILABILITY

		8.5 x 8.5 glossy	8.5 x 8.5 matte	13.35 x 13.35 glossy	6 x 24 glossy	1.75 x 8.5 glossy buttrose	1.75 x 8.5 matte buttrose
 Bianco		✓	✓	✓	✓	✓	✓
 Nero		✓	✓	✓	✓	✓	✓
 Grigio		✓	✓		✓	✓	✓
 Cenere		✓	⊘		✓	✓	
 Blu		✓		⊘	✓	✓	
 Smeraldo		✓		⊘	✓	✓	
 Azzurro		⊘		⊘	⊘		
 Acquamarina		⊘		⊘	⊘		
 Giallo		⊘			⊘		
 Arancio		⊘			⊘		
 Rosso		⊘			⊘		

TECHNICAL INFORMATION

TILE SIZES

Nominal	Shape	Finish	Thickness
8.5 x 8.5		Matte	9 mm
8.5 x 8.5		Glossy	9 mm
13.35 x 13.35		Glossy	9 mm
6 x 24		Glossy	9 mm
1.75 x 8.5 Bullnose		Matte	9 mm
1.75 x 8.5 Bullnose		Glossy	9 mm

PERFORMANCE DATA

CHARACTERISTIC	NORMS	RESULTS
Water Absorption	ISO 10545-3	≤ 0.5 %
Abrasion Resistance (Glazed)	ISO 10545-7	3 / 4
Dynamic Coefficient of Friction Wet	AcuTest	0.21 (Glossy) ≥ 0.42 (Matte)
Dimensions Range	ISO 10545-2	Conforms

SHADE VARIATION



V2 - SLIGHT VARIATION
Clearly distinguishable differences in texture and/or pattern within similar colors.

WEAR CODE

Nero, Grigio, Rosso, Giallo: 3 - Rated for walls and residential floor applications only.
All Others: 4 - Rated for all residential and light commercial applications.

APPLICATIONS

	RESIDENTIAL	LIGHT COMMERCIAL	COMMERCIAL
FLOORS	X	X <small>(all except Nero, Grigio, Rosso, Giallo)</small>	
WALLS / BACKSPLASH	X	X	X
POOL DECKING			
EXTERNAL USE - FROST PROOF			

X - Has been approved for this application.
* - Information is available upon request.

NOTES

It is not recommended to stagger any tile longer than 18" more than 1/3 the length of the tile.

Minimum Grout Joint Recommendation: 3/16"

Always inspect materials prior to installation.

Always mix 2-3 cartons at a time while installing to insure the best blend.

All product images are representative only. Variation in color and shading is to be expected. Final selection should be made from actual tile samples.