



Essex | Glazed Porcelain

AVAILABLE SIZES

8x48 rectified	8x48 lux rectified
-------------------	--------------------------

DESCRIPTION


Essex wood porcelain tile is one of the most unique Italian porcelain tile lines available today. The tone-on-tone color and sheen veining offered in this wood look tile series will enhance your space with personality and charm. Available in an 8" x 48" rectangular tile format, Essex is suitable for all floor and wall tile applications in any room you desire.

COLORS



TECHNICAL INFORMATION

TILE SIZES

Nominal	Shape	Finish	Thickness
8 x 48 rectified		Matte / Lux	10 mm

PERFORMANCE DATA

CHARACTERISTIC	NORMS	RESULTS
Water Absorption	ISO 10545-3	≤ 0.5 %
PEI Abrasion Resistance (Glazed)	ISO 10545-7	Soft, White = 5; All Others = 4
Breaking Strength	ISO 10545-4	> 38 N/mm2
Dynamic Coefficient of Friction Wet	AcuTest	≥ 0.60
Dimensions Range	ISO 10545-2	Conforms
Frost Resistance	ISO 10545-12	Frost Proof
Chemical Resistance - Household Chemicals	ISO 10545-13	Resistant
Chemical Resistance - Low Concentration of Acids and Bases	ISO 10545-13	Resistant
Thermal Shock Resistance	ISO 10545-9	Resistant
Resistance to Stains	ISO 10545-14	Class 4
Crazing Resistance of Glazed Tiles	ISO 10545-11	Resistant

SHADE VARIATION



V3 - MODERATE VARIATION

While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece may vary significantly. For example "that little bit of color" on one piece of tile may be the primary color on the next piece.

WEAR CODE

White / Soft: 5 - Rated for all residential and commercial applications.

Sugar / Nut / Cherry / Blue: 4 - Rated for all residential and light commercial applications.

APPLICATIONS

	RESIDENTIAL	LIGHT COMMERCIAL	COMMERCIAL
FLOORS	✗	✗	
WALLS / BACKSPLASH	✗	✗	✗
POOL DECKING	*	*	
EXTERNAL USE - FROST PROOF	*	*	

✗ - Has been approved for this application.

* - Information is available upon request.

NOTES

It is not recommended to stagger any tile longer than 18" more than 1/3 the length of the tile.

Minimum Grout Joint Recommendation: 1/8"

Always inspect materials prior to installation.

Always mix 2-3 cartons at a time while installing to insure the best blend.

All product images are representative only. Variation in color and shading is to be expected. Final selection should be made from actual tile samples.