




Judi | Ceramic / Porcelain




AVAILABLE SIZES



DESCRIPTION




Judi porcelain tile offers a unique shimmer effect on a subtle, tone-on-tone textured surface. This very affordable Spanish tile series has a high-quality porcelain floor tile in 13" x 13" along with a ceramic wall tile in 10" x 16", available in both Grey and Cream colors. Mosaic tiles are also available for the series. Judi porcelain tile is perfect for any residential or light commercial space.

COLORS




TECHNICAL INFORMATION

TILE SIZES

Nominal	Shape	Material	Thickness
10 x 16 Wall		Ceramic	8.6 mm
13 x 13		Porcelain	8.4 mm
2 x 2 Mosaic		Porcelain	8.4 mm

COORDINATING TRIM

Nominal	Shape	Material	Thickness
2 x 10 Wall Bullnose		Ceramic	8.6 mm

PERFORMANCE DATA

CHARACTERISTIC	NORMS	RESULTS
Water Absorption	ISO 10545-3	0.49
Abrasion Resistance (Glazed)	ISO 10545-7	4
Breaking Strength	ISO 10545-4	≥ 35 N/mm ²
Dynamic Coefficient of Friction Wet	AcuTest	0.16
Dimensions Range	ISO 10545-2	Conforms
Facial Range of Thickness	ISO 10545-2	Conforms
Warpage (Diagonal)	ISO 10545-2	Conforms
Wedging	ISO 10545-2	Conforms
Frost Resistance	ISO 10545-12	Frost Resistant
Scratch Hardness	MOHS	8

SHADE VARIATION



V2 - SLIGHT VARIATION
Clearly distinguishable differences in texture and/or pattern within similar colors.

WEAR CODE

13 x 13 / 2 x 2 Mosaic: 4 - Rated for all residential and light commercial applications.
10 x 16 / 2 x 10 Bullnose: 1 - Rated for wall applications only.

APPLICATIONS

	RESIDENTIAL	LIGHT COMMERCIAL	COMMERCIAL
FLOORS	X	X	
WALLS / BACKSPLASH	X	X	X
POOL DECKING			
EXTERNAL USE - FROST PROOF			

X - Has been approved for this application.
* - Information is available upon request.

NOTES

Minimum Grout Joint Recommendation: 3/16"

Always inspect materials prior to installation.

Always mix 2-3 cartons at a time while installing to insure the best blend.

All product images are representative only. Variation in color and shading is to be expected. Final selection should be made from actual tile samples.