

# Marble Look

GLAZED PORCELAIN

BEST TILE® / BESTTILE.COM

# Calacatta Hex



## COLORS, SIZES & AVAILABILITY

NOMINAL SIZE	FINISH	THICKNESS	GROUT JOINT	GOLD	SILVER
20.5 x 24 Hexagon	Matte	9.4 mm	3/16"	✓	✓

✓ Stock Item. ⚠ Non-Stock Item. Requires Extra Lead Time.

## TECH INFO

R = Residential, LC = Light Commercial, C = Commercial

<b>ORIGIN:</b> Spain <b>SHADE VARIATION:</b> V3 - Moderate Variation <b>WEAR RATING:</b> 4 - Walls + Residential / Light Commercial Floor Applications Layout and blend cartons prior to installation.	RECOMMENDED APPLICATIONS	R	LC	C
	FLOORS	●	●	
	WALLS / BACKSPLASH	●	●	●
	POOL DECKING			
	EXTERNAL USE - FROST PROOF	*		

● Approved for this application. \* Discuss proper installation method with your Sales Representative.

## TILE PERFORMANCE DATA

TECHNICAL FEATURE	NORMS	RESULTS
Water Absorption	ISO 10545-3	< 0.5 %
Abrasion Resistance (Glazed)	ISO 10545-7	4
Breaking Strength	ISO 10545-4	≥ 1300 N
Dynamic Coefficient of Friction Wet	AcuTest	> 0.70
Dimensions Range	ISO 10545-2	Conforms
Frost Resistance	ISO 10545-12	Frost Proof
Chemical Resistance - Household Chemicals	ISO 10545-13	Resistant
Chemical Resistance - Low Concentration of Acids and Bases	ISO 10545-13	Resistant
Scratch Hardness	MOHS	7
Resistance to Stains	ISO 10545-14	Min. Class 3

Always inspect materials prior to installation. Always mix 2-3 cartons at a time while installing to ensure the best blend. All product images are representative only. Variation in color and shading is to be expected. Final selection should be made from actual tile samples.