

Atenas | Glazed Porcelain



AVAILABLE SIZES



DESCRIPTION

Atenas is a Spanish porcelain series that offers a high-end wood look at an affordable price. With subtle tone-on-tone movement in grey, taupe and beige, Atenas marries two distinct American looks: wood plank flooring and neutral tones. This 9" x 48" plank format, replicating a refined modern wood, is suitable for all residential and light commercial applications.

COLORS

beige



gris



taupe



TECHNICAL INFORMATION

TILE SIZES

Nominal	Shape	Finish	Thickness
9 x 48		Matte	10 mm

PERFORMANCE DATA

CHARACTERISTIC	NORMS	RESULTS
Water Absorption	ISO 10545-3	≤ 0.5 %
PEI Abrasion Resistance (Glazed)	ISO 10545-7	4
Breaking Strength	ISO 10545-4	> 38 N/mm ²
Dynamic Coefficient of Friction Wet	AcuTest	0.49
Dimensions Range	ISO 10545-2	Conforms
Frost Resistance	ISO 10545-12	Frost Proof
Chemical Resistance - Household Chemicals	ISO 10545-13	GLA/GHA
Chemical Resistance - Low Concentration of Acids and Bases	ISO 10545-13	GLA/GHA
Linear Thermal Expansion	ISO 10545-8	Conforms
Thermal Shock Resistance	ISO 10545-9	Passes Standard Test
Resistance to Stains	ISO 10545-14	Class 5

SHADE VARIATION



V3 - MODERATE VARIATION

While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece may vary significantly. For example "that little bit of color" on one piece of tile may be the primary color on the next piece.

WEAR CODE

4 - Rated for all residential and light commercial applications.

APPLICATIONS

	RESIDENTIAL	LIGHT COMMERCIAL	COMMERCIAL
FLOORS	✘	✘	
WALLS / BACKSPLASH	✘	✘	✘
POOL DECKING			
EXTERNAL USE - FROST PROOF	✘	✘	

✘ - Has been approved for this application.

* - Information is available upon request.

NOTES

It is not recommended to stagger any tile longer than 18" more than 1/3 the length of the tile.

Always inspect materials prior to installation.

Always mix 2-3 cartons at a time while installing to insure the best blend.

All product images are representative only. Variation in color and shading is to be expected. Final selection should be made from actual tile samples.