




## Bar Harbor Glazed Porcelain



#### AVAILABLE SIZES



#### DESCRIPTION

Bar Harbor is a glazed porcelain blend of mixed wood looks highlighting the grain, wear and structure of reclaimed planks. Two large formats (6.5" or 9.75" x 39.5") can be combined for a true craftsman look, while 4" x 13" mini planks can create a herringbone or parquet look. The unique 4" Hexagon mosaic is perfect for accents and shower floors. Bar Harbor porcelain tile is available in three robust shades and is suitable for all residential and most commercial applications.

COLORS



# TECHNICAL INFORMATION

#### TILE SIZES

Nominal	Shape	Finish	Thickness
4 x 13		Matte	10.5 mm
6.5 x 39.5		Matte	10.5 mm
9.75 x 39.5		Matte	10.5 mm
4" Hexagon Mosaic		Matte	10.5 mm

### PERFORMANCE DATA

CHARACTERISTIC	NORMS	RESULTS
Water Absorption	ISO 10545-3	0.10%
PEI Abrasion Resistance (Glazed)	ISO 10545-7	4 / 5
Breaking Strength	ISO 10545-4	> 38 N/mm2
Dynamic Coefficient of Friction Wet	AcuTest	0.42
Frost Resistance	ISO 10545-12	Frost Proof
Chemical Resistance - Household Chemicals	ISO 10545-13	GA
Chemical Resistance - Low Concentration of Acids and Bases	ISO 10545-13	GLA
Scratch Hardness	MOHS	6
Resistance to Stains	ISO 10545-14	Class 5

#### SHADE VARIATION



V4 - RANDOM VARIATION Random color differences from tile to tile, so that one tile may have totally different colors from that of other tiles. Thus the final installation will be unique.

#### WEAR CODE

Brown: 4 - Rated for all residential and light commercial applications.

Beige / Grey: 5 - Rated for all residential and commercial applications.

## **APPLICATIONS**

	RESIDENTIAL	LIGHT COMMERCIAL	COMMERCIAL
FLOORS	×	×	×
WALLS / BACKSPLASH	×	×	×
POOL DECKING	*		
EXTERNAL USE - FROST PROOF	*		
	<ul> <li>+ Has been approved for this application.</li> <li>Information is available upon request.</li> </ul>		

#### **NOTES**

The factory recommends that the 39.5" long planks be staggered NO MORE than 8".

Always inspect materials prior to installation.

Always mix 2-3 cartons at a time while installing to insure the best blend.

All product images are representative only. Variation in color and shading is to be expected. Final selection should be made from actual tile samples.

