



Aterra | Glazed Porcelain

AVAILABLE SIZES



DESCRIPTION

Cherry wood tile leads a stunning range of natural wood colors along with oak, walnut, grey, and white. Aterra offers the look of natural wood with the strength, durability and low maintenance of porcelain tile. A high quality Italian technical porcelain series with a refined hand-scraped surface detail that conveys elegance and warmth to any residential or commercial space.

COLORS



TECHNICAL INFORMATION

TILE SIZES

Nominal	Shape	Finish	Thickness
8 x 48 rectified		Matte	10.5 mm

PERFORMANCE DATA

CHARACTERISTIC	NORMS	RESULTS
Water Absorption	ISO 10545-3	≤ 0.5 %
PEI Abrasion Resistance (Glazed)	ISO 10545-7	4 / 5
Breaking Strength	ISO 10545-4	≥ 35 N/mm ²
Dynamic Coefficient of Friction Wet	AcuTest	0.45
Dimensions Range	ISO 10545-2	Conforms
Frost Resistance	ISO 10545-12	Frost Proof
Chemical Resistance - Household Chemicals	ISO 10545-13	GA
Chemical Resistance - Low Concentration of Acids and Bases	ISO 10545-13	GA
Thermal Shock Resistance	ISO 10545-9	Resistant
Resistance to Stains	ISO 10545-14	Class 5

RECYCLED CONTENT



Aterra grafite contains 16% Recycled Content, all other colors contain 11%.

SHADE VARIATION



V3 - MODERATE VARIATION

While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece may vary significantly. For example "that little bit of color" on one piece of tile may be the primary color on the next piece.

WEAR CODE

Gesso / Juta: 5 - Rated for all residential and commercial applications.

Cuoio / Tabacco / Grafite: 4 - Rated for all residential and light commercial applications.

APPLICATIONS

	RESIDENTIAL	LIGHT COMMERCIAL	COMMERCIAL
FLOORS	✘	✘	Gesso / Juta
WALLS / BACKSPLASH	✘	✘	✘
POOL DECKING	*		
EXTERNAL USE - FROST PROOF	*		

✘ - Has been approved for this application.

* - Information is available upon request.

NOTES

It is not recommended to stagger any tile longer than 18" more than 1/3 the length of the tile.

Grout joint recommendation: 1/8" minimum

Always inspect materials prior to installation.

Always mix 2-3 cartons at a time while installing to insure the best blend.

All product images are representative only. Variation in color and shading is to be expected. Final selection should be made from actual tile samples.