



AVAILABLE SIZES

12x24

3x24 Bullnose

DESCRIPTION

This Italian porcelain tile series mixes "layers" of design elements, including linen fabric looks, tone-on-tone coloring and shimmering surface accents. A tile series that is defined by multiple modern trends, this high-quality technical porcelain tile is available in a 12" x 24" format.

COLORS



TECHNICAL INFORMATION

TILE SIZES

Nominal	Shape	Finish	Thickness
12 x 24		Matte	9.5 mm

COORDINATING TRIM

Nominal	Shape	Finish	Thickness
3 x 24 Bullnose		Matte	9.5 mm

PERFORMANCE DATA

CHARACTERISTIC	NORMS	RESULTS	
Water Absorption	ISO 10545-3	0.05 %	
Deep Abrasion	ISO 10545-6	≤ 145 mm3	
PEI Abrasion Resistance (Glazed)	ISO 10545-7	5	
Breaking Strength	ISO 10545-4	47 N/mm2	
Wet DCOF	AcuTest	≥ 0.42	
Dimensions Range	ISO 10545-2	Conforms	
Frost Resistance	ISO 10545-12	Frost Proof	
Chemical Resistance (Household Chemicals)	ISO 10545-13	Resistant	
Chemical Resistance - Low Concentration of Acids and Bases	ISO 10545-13	Resistant	
Thermal Shock Resistance	ISO 10545-9	Resistant	
Resistance to Stains	ISO 10545-14	Cleanable	

SHADE VARIATION



V1 - UNIFORM APPEARANCE

Differences among pieces from the same production run are minimal.

WEAR CODE

5 - Rated for all residential and commercial applications.

APPLICATIONS

	RESIDENTIAL	LIGHT COMMERCIAL	COMMERCIAL
FLOORS	×	×	×
WALLS / BACKSPLASH	×	×	×
POOL DECKING	*	*	
EXTERNAL USE - FROST PROOF	*	*	*

x - Has been approved for this application.

* - Information is available upon request.

NOTES

It is not recommended to stagger any tile longer than 18" more than 1/3 the length of the tile.

Minimum Grout Joint Recommendation: 1/8"

Always inspect materials prior to installation.

Always mix 2-3 cartons at a time while installing to insure the best blend.

All product images are representative only. Variation in color and shading is to be expected. Final selection should be made from actual tile samples.

