

Trace | Porcelain





















AVAILABLE SIZES

<div>12x12*</div> <div>Only available in: mint</div>	
12x24	24x24*
10x30 Not available in: mint	30x30* Not available in: mint
10x60* Not available in: mint or bronze	30x60* Not available in: mint or bronze
1.375x1.375 Mosaic	12x24 random mosaic*
3x24 Bullnose	

DESCRIPTION

Dramatic and substantial, Trace porcelain is inspired by the aging materials of history's great structures. A modern recreation of colors and textures, Trace's combination of bronzed metal and opaque cement screens offers an industrial look to today's commercial and residential settings. The only Italian porcelain that has masterfully achieved both a Copper and a unique Oxidized Copper look, Trace is available in sizes from 12" x 24" to 30" x 60" - that exceed technical requirements.

COLORS










vitro	allumina	iron	corten	bronze	mint
					
					
					
					

***Non-stock item, 6-8 week lead time required.**


mint deco available in 12x12 & 24x24*

TECHNICAL INFORMATION

TILE SIZES

Nominal	Shape	Finish	Thickness
12 x 12		Matte	10 mm
12 x 24		Matte	10 mm
24 x 24		Matte	10 mm
10 x 30		Matte	10 mm
30 x 30		Matte	10 mm
10 x 60		Matte	10 mm
30 x 60		Matte	10 mm
1.375 x 1.375 Mosaic		Matte	10 mm
12 x 24 Random Mosaic		Matte	10 mm

COORDINATING TRIM

Nominal	Shape	Finish	Thickness
3 x 24 Bullnose		Matte	10 mm

PERFORMANCE DATA

CHARACTERISTIC	NORMS	RESULTS
Water Absorption	ISO 10545-3	≤ 0.05 %
Deep Abrasion	ISO 10545-6	≤ 145 mm3
PEI Abrasion Resistance (Glazed)	ISO 10545-7	NA
Breaking Strength	ISO 10545-4	47 N/mm2
Dynamic Coefficient of Friction Wet	AcuTest	≥ 0.42
Static Coefficient of Friction Wet	C1028	≥ 0.60
Dimensions Range	ISO 10545-2	Conforms
Frost Resistance	ISO 10545-12	Frost Proof
Chemical Resistance - Household Chemicals	ISO 10545-13	Resistant
Chemical Resistance - Low Concentration of Acids and Bases	ISO 10545-13	Resistant
Linear Thermal Expansion	ISO 10545-8	6
Thermal Shock Resistance	ISO 10545-9	Resistant
Resistance to Stains	ISO 10545-14	Cleanable

SHADE VARIATION



V3 - MODERATE VARIATION
While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece may vary significantly. For example "that little bit of color" on one piece of tile may be the primary color on the next piece.

WEAR CODE

5 - Rated for all residential and commercial applications.

APPLICATIONS

	RESIDENTIAL	LIGHT COMMERCIAL	COMMERCIAL
FLOORS	✕	✕	✕
WALLS / BACKSPLASH	✕	✕	✕
POOL DECKING	*	*	
EXTERNAL USE - FROST PROOF	*	*	

✕ - Has been approved for this application.
* - Information is available upon request.

NOTES

It is not recommended to stagger any tile longer than 18" more than 1/3 the length of the tile.

Always inspect materials prior to installation.

Always mix 2-3 cartons at a time while installing to insure the best blend.