

Stone Look

COLOR BODY • PORCELAIN

Carlisle

COLORS, SIZES & AVAILABILITY

NOMINAL SIZE	FINISH	THICKNESS	GROUT JOINT	ALABASTER	GREIGE	SILVER	WINTERGREEN
12 x 24 Rectified	Matte	9 mm	1/8"	✓	✓	✓	✓
12 x 24 Rectified	Lappato	9 mm	1/8"	✓	✓	✓	✓
24 x 24 Rectified	Matte	9 mm	1/8"	✓	✓	✓	✓
24 x 24 Rectified	Lappato	9 mm	1/8"	✓	✓	✓	✓
24 x 48 Rectified	Matte	9 mm	1/8"	⊘	⊘	⊘	⊘
24 x 48 Rectified	Lappato	9 mm	1/8"	⊘	⊘	⊘	⊘
24 x 48 Rectified	LUX	9 mm	1/8"	⊘	⊘	⊘	⊘
2 x 3 Brick Mosaic	Matte	9 mm	N/A	✓	✓	✓	✓
3 x 3.5 Hexagon Mosaic	Matte	9 mm	N/A	✓	✓	✓	✓
3 x 24 Bullnose	Matte	9 mm	1/8"	✓	✓	✓	✓
3 x 24 Bullnose	Lappato	9 mm	1/8"	⊘	⊘	⊘	⊘

✓ Stock Item. ⊘ Non-Stock Item. Requires Extra Lead Time.

TECH INFO

R = Residential, LC = Light Commercial, C = Commercial

ORIGIN: Italy SHADE VARIATION: V3 - Moderate Variation WEAR RATING: Lappato: 4 - Walls + Residential / Light Commercial Floor Applications; Matte: 5 - Walls + Residential / Commercial Floor Applications It is not recommended to stagger any tile longer than 15" more than 1/3 the length of the tile.	RECOMMENDED APPLICATIONS	R	LC	C
	FLOORS	●	●	✦
	WALLS / BACKSPLASH	●	●	●
	POOL DECKING			
	EXTERNAL USE - FROST PROOF	*	*	

● Approved for this application. ✦ Matte approved for this application. * Discuss proper installation method with your Sales Representative.

TILE PERFORMANCE DATA

TECHNICAL FEATURE	NORMS	RESULTS
Water Absorption	ISO 10545-3	≤ 0.5 %
Breaking Strength	ISO 10545-4	> 40 N/mm ²
Dynamic Coefficient of Friction Wet	AcuTest	≥ 0.42 (Matte)
Thickness Dimension	ISO 10545-2	Compliant
Frost Resistance	ISO 10545-12	Frost Proof
Chemical Resistance - Household Chemicals	ISO 10545-13	Min. UB
Chemical Resistance - Low Concentration of Acids and Bases	ISO 10545-13	Min. UB