Terra Cotta Look

GLAZED PORCELAIN

Etruscan



COLORS.	SIZES &	AVAILABILITY

					0	MARCHE	CAN	R A	∀ 0	0 B	Σ
	NOMINAL SIZE	FINISH	THICKNESS	GROUT JOINT	LAZIO	MAR	TOSC,	UMBRIA	DECO	DECO	DECO
	8 x 8	Matte	9 mm	3/16" *	√	✓	✓	/	√	√	
1	8 x 16	Matte	9 mm	3/16" *	√	✓	✓	✓			
	16 x 16	Matte	9 mm	3/16" *	✓	✓	✓	V			
	9 x 10 Hexagon	Matte	10 mm	3/16"	✓	~	✓	✓			✓
	Hexagon Mosaic	Matte	10 mm	N/A	✓	~	✓	✓			
	3 x 16 Bullnose	Matte	9 mm	3/16"	✓	✓	✓	✓			

^{*}Grout joints in modular pattern may need to be larger.

TECH INFO

	Г	7	- 1	1 /	Г	\cup

R = Residential, LC = Light Commercial, C = Commercial

ORIGIN: Italy	RECOMMENDED APPLICATIONS	R	LC	С
SHADE VARIATION: V3 - Moderate Variation; Marche: V4 WEAR RATING: Lazio; 5 - Rated for all residential and commercial	FLOORS	•	•	+
applications; All others: 4 - Rated for all residential and light commercial applications	WALLS / BACKSPLASH	•		•
It is not recommended to stagger any tile longer than 15" more than 1/3 the length of the tile.	POOL DECKING	*	*	
are engar or are are.	EXTERNAL USE - FROST PROOF	*	*	

Approved for this application.

TILE PERFORMANCE DATA

TECHNICAL FEATURE	NORMS	RESULTS		
Water Absorption	ISO 10545-3	≤ 0.5 %		
Abrasion Resistance (Glazed)	ISO 10545-7	5 - Lazio; 4 - All Others		
Breaking Strength	ISO 10545-4	≥ 35 N/mm2		
Dynamic Coefficient of Friction Wet	AcuTest	0.77; Decos: 0.56		
Dimensions Range	ISO 10545-2	Conforms		
Frost Resistance	ISO 10545-12	Frost Proof		
Chemical Resistance - Household Chemicals	ISO 10545-13	Min. Class B		
Chemical Resistance - Low Concentration of Acids and Bases	ISO 10545-13	Min. Class B		
Thermal Shock Resistance	ISO 10545-9	Resists		
Resistance to Stains	ISO 10545-14	Class 5		
Crazing Resistance of Glazed Tiles	ISO 10545-11	Resistant		







[✓] Stock Item. U Non-Stock Item, Requires Extra Lead Time

[◆] Lazio approved for this application

Discuss proper installation method with your Sales Representative.