

# Quartzite Look

GLAZED PORCELAIN

BEST TILE® / BESTTILE.COM

# Riva Stone

## COLORS, SIZES & AVAILABILITY

NOMINAL SIZE	FINISH	THICKNESS	GROUT JOINT	GRAY	OFF WHITE	SAND
12 x 24	Matte	9.5 mm	3/16"	✓	✓	✓
2 x 2 Mosaic	Matte	9.5 mm	3/16"	✓	✓	✓

✓ Stock Item. ⚠ Non-Stock Item. Requires Extra Lead Time.

## TECH INFO

R = Residential, LC = Light Commercial, C = Commercial

<b>ORIGIN:</b> Brazil <b>SHADE VARIATION:</b> V2 - Slight Variation <b>WEAR RATING:</b> Class 4 - Rated for residential and light commercial applications It is not recommended to stagger any tile longer than 15" more than 1/3 the length of the tile.	RECOMMENDED APPLICATIONS	R	LC	C
	FLOORS	●	●	
	WALLS / BACKSPLASH	●	●	●
	POOL DECKING	*	*	
	EXTERNAL USE - FROST PROOF	*	*	

● Approved for this application. \* Discuss proper installation method with your Sales Representative.

## TILE PERFORMANCE DATA

TECHNICAL FEATURE	NORMS	RESULTS
Water Absorption	ISO 10545-3	≤ 0.5 %
Abrasion Resistance (Glazed)	ISO 10545-7	4
Breaking Strength	ISO 10545-4	≥ 250 lbf
Dynamic Coefficient of Friction Wet	AcuTest	≥ 0.45
Frost Resistance	ISO 10545-12	Frost Proof
Chemical Resistance - Household Chemicals	ISO 10545-13	Class B
Chemical Resistance - Low Concentration of Acids and Bases	ISO 10545-13	Class B
Resistance to Stains	ISO 10545-14	Class A

Always inspect materials prior to installation. Always mix 2-3 cartons at a time while installing to insure the best blend. All product images are representative only. Variation in color and shading is to be expected. Final selection should be made from actual tile samples.