


Sorriso | Glazed Ceramic



AVAILABLE SIZES




DESCRIPTION

The Look you want. The Price you love. For your next budget conscious project, look no further than Sorriso ceramic. Sorriso offers two must haves for your next tile installation, a beautiful stone look with an affordable price tag!

Manufacturer direct pricing of \$1.99 a square foot allows us to offer Sorriso at this exceptional low cost. Imported from Spain, Sorriso is available in three timeless colors; bone, gris, and noce, each with swirling travertine veining. Sorriso 18x18 ceramic is ideal for all residential and light commercial applications.

COLORS

bone



gris




noce



TECHNICAL INFORMATION

TILE SIZES

Nominal	Shape	Finish	Thickness
18 x 18		Matte	9 mm

PERFORMANCE DATA

CHARACTERISTIC	NORMS	RESULTS
Water Absorption	ISO 10545-3	3% < E ≤ 6%
PEI Abrasion Resistance (Glazed)	ISO 10545-7	4
Breaking Strength	ISO 10545-4	≥ 1500 N
Static Coefficient of Friction Wet	C1028	0.67
Dimensions Range	ISO 10545-2	±0.5% Max
Facial Range of Thickness	C499	≤ 0.40 %
Frost Resistance	ISO 10545-12	No
Chemical Resistance - Household Chemicals	ISO 10545-13	GB
Chemical Resistance - Low Concentration of Acids and Bases	ISO 10545-13	GLA/GHA
Linear Thermal Expansion	ISO 10545-8	Test Method Available
Thermal Shock Resistance	ISO 10545-9	Resistant
Resistance to Stains	ISO 10545-14	Class 4
Crazing Resistance of Glazed Tiles	ISO 10545-11	Resistant

SHADE VARIATION



V2 - SLIGHT VARIATION
Clearly distinguishable differences in texture and/or pattern within similar colors.

WEAR CODE

4 - Rated for all residential and light commercial applications.

APPLICATIONS

	RESIDENTIAL	LIGHT COMMERCIAL	COMMERCIAL
FLOORS	✕	✕	
WALLS / BACKSPLASH	✕	✕	✕
POOL DECKING			
EXTERNAL USE - FROST PROOF			

✕ - Has been approved for this application.
* - Information is available upon request.

NOTES

It is not recommended to stagger any tile longer than 18" more than 1/3 the length of the tile.

Always inspect materials prior to installation.

Always mix 2-3 cartons at a time while installing to insure the best blend.