







Appian Stones | Glazed Porcelain



AVAILABLE SIZES







DESCRIPTION

Appian Stones is an upscale Italian porcelain tile series that showcases the beautiful veining patterns of four elegant Italian marble stone looks in a consistent white or black color tone. Blending the look of Carrara Marble, Statuario Marble, Gioia Marble, and Venatino Marble, the series offers a singular, hard-to-copy expression of upscale Italian marble design for your room. Versatility is achieved with multiple porcelain tile sizes and a stunning collection of marble stone look mosaics.

COLORS








black

white




TECHNICAL INFORMATION

TILE SIZES

Nominal	Shape	Finish	Thickness
4x8		Matte	10 mm
8x8		Matte	10 mm
8x16		Matte	10 mm
16x16		Matte	10 mm
2x2 Mosaic		Matte	10 mm
Basketweave (Intreccio) Mosaic		Matte	10 mm
Hexagon Mosaic		Matte	10 mm

COORDINATING TRIM

Nominal	Shape	Finish	Thickness
3 x 24 Bullnose		Matte	10 mm

PERFORMANCE DATA

CHARACTERISTIC	NORMS	RESULTS
Water Absorption	ISO 10545-3	0.08 %
PEI Abrasion Resistance (Glazed)	ISO 10545-7	White = 5; Black = 3
Breaking Strength	ISO 10545-4	≥ 50 N/mm ²
Dynamic Coefficient of Friction Wet	AcuTest	0.57
Frost Resistance	ISO 10545-12	Frost Proof
Resistance to Stains	ISO 10545-14	Class 4

SHADE VARIATION



V3 - MODERATE VARIATION

While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece may vary significantly. For example "that little bit of color" on one piece of tile may be the primary color on the next piece.

WEAR CODE

White: 5 - Rated for all residential and commercial applications.

Black: 3 - Rated for residential applications only.

APPLICATIONS

	RESIDENTIAL	LIGHT COMMERCIAL	COMMERCIAL
FLOORS	✗	✗ (White Only)	
WALLS / BACKSPLASH	✗	✗	✗
POOL DECKING			
EXTERNAL USE - FROST PROOF	* (White Only)		

✗ - Has been approved for this application.

* - Information is available upon request.

NOTES

Minimum Grout Joint Recommendation: 3/16"

Always inspect materials prior to installation.

Always mix 2-3 cartons at a time while installing to insure the best blend.

All product images are representative only. Variation in color and shading is to be expected. Final selection should be made from actual tile samples.