

# Lochwood Porcelain

STONEPEAK  
high tech porcelain



### AVAILABLE SIZES

4x48	8x48	12x48
		Arrow Herringbone Mosaic on 12x12 Sheet
		3x6 Parquet Mosaic on 12x12 sheet
3x24 Bullnose		6x12 Cove Base

## DESCRIPTION



A high-quality porcelain tile made in the USA. Lochwood is a color body wood tile series that emphasizes American wood flooring color tones, with an emphasis on rich, brown wood tones. Available in three exciting rectangular tile sizes, Lochwood offers multiple wood plank looks for your project and is also available in a beautiful chevron mosaic and parquet mosaic option.

## COLORS


fauna




auburn



cedar








charcoal





# TECHNICAL INFORMATION

## TILE SIZES

Nominal	Shape	Finish	Thickness
4 x 48 Rectified		Matte	8 mm
8 x 48 Rectified		Matte	8 mm
12 x 48 Rectified		Matte	8 mm
Arrow Herringbone Mosaic		Matte	8 mm
3 x 6 Parquet Mosaic		Matte	8 mm

## COORDINATING TRIM

Nominal	Shape	Finish	Thickness
3 x 24 Bullnose		Matte	8 mm
6 x 12 Cove Base		Matte	7.5 mm

## PERFORMANCE DATA

CHARACTERISTIC	NORMS	RESULTS
Water Absorption	C373	≤ 0.1 %
PEI Abrasion Resistance (Glazed)	CI027	Class 3
Breaking Strength	C648	≥ 400 lbs
Bond Strength	C482	≥ 200 psi
Wet DCOF	AcuTest	≥ 0.60
Thickness Dimension	C499	In Accordance
Facial Dimension	C499	In Accordance
Warpage Diagonal	C485	In Accordance
Wedging Average	C502	In Accordance
Frost Resistance	CI026	Frost Proof
Chemical Resistance	C650	Class A
Scratch Hardness	MOHS	≥ 7

## RECYCLED CONTENT



Contains 40% Pre-Consumer Recycled Content.

## SHADE VARIATION



### V3 - MODERATE VARIATION

While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece may vary significantly. For example "that little bit of color" on one piece of tile may be the primary color on the next piece.

## WEAR CODE

3 - Rated for residential applications only.

## APPLICATIONS

	RESIDENTIAL	LIGHT COMMERCIAL	COMMERCIAL
FLOORS	✗		
WALLS / BACKSPLASH	✗	✗	✗
POOL DECKING	*		
EXTERNAL USE - FROST PROOF			

✗ - Has been approved for this application.

\* - Information is available upon request.

## NOTES

It is not recommended to stagger any tile longer than 18" more than 1/3 the length of the tile.

Minimum Grout Joint Recommendation: 1/8"

Always inspect materials prior to installation.

Always mix 2-3 cartons at a time while installing to insure the best blend.

All product images are representative only. Variation in color and shading is to be expected. Final selection should be made from actual tile samples.

