



# Portraits | Porcelain



## AVAILABLE SIZES

12x24 Rectified


2x2 Mosaic  
on 12x12 sheet

3x24 Bullnose

## DESCRIPTION



This Italian porcelain tile series celebrates seven stone looks, each from a unique global destination. Marble, Limestone and Slate are all represented in modern reflections of subtle colors and low variation. A tile series that puts elegant stone flooring looks on high-quality porcelain tile, Portraits is available in a 12" x 24" format with a 2" mosaic option.

## COLORS




# TECHNICAL INFORMATION

## TILE SIZES

Nominal	Shape	Finish	Thickness
12 x 24 Rectified		Matte	9.5 mm
2 x 2 Mosaic		Matte	9.5 mm

## COORDINATING TRIM

Nominal	Shape	Finish	Thickness
3 x 24 Bullnose		Matte	9.5 mm

## PERFORMANCE DATA

CHARACTERISTIC	NORMS	RESULTS
Water Absorption	ISO 10545-3	0.05%
Deep Abrasion	ISO 10545-6	145 mm <sup>3</sup>
PEI Abrasion Resistance (Glazed)	ISO 10545-7	5
Breaking Strength	ISO 10545-4	47 N/mm <sup>2</sup>
Dynamic Coefficient of Friction Wet	AcuTest	0.68
Dimensions Range	ISO 10545-2	Conforms
Frost Resistance	ISO 10545-12	Frost Proof
Chemical Resistance (Household Chemicals)	ISO 10545-13	Resistant
Chemical Resistance - Low Concentration of Acids and Bases	ISO 10545-13	Resistant
Thermal Shock Resistance	ISO 10545-9	Resistant
Resistance to Stains	ISO 10545-14	Cleanable

## SHADE VARIATION



### V3 - MODERATE VARIATION

While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece may vary significantly. For example "that little bit of color" on one piece of tile may be the primary color on the next piece.

## WEAR CODE

5 - Rated for all residential and commercial applications.

## APPLICATIONS

	RESIDENTIAL	LIGHT COMMERCIAL	COMMERCIAL
FLOORS	✘	✘	✘
WALLS / BACKSPLASH	✘	✘	✘
POOL DECKING	*	*	*
EXTERNAL USE - FROST PROOF	*	*	*

✘ - Has been approved for this application.

\* - Information is available upon request.

## NOTES

It is not recommended to stagger any tile longer than 18" more than 1/3 the length of the tile.

Grout Joint Recommendation: 1/8"

Always inspect materials prior to installation.

Always mix 2-3 cartons at a time while installing to insure the best blend.

All product images are representative only. Variation in color and shading is to be expected. Final selection should be made from actual tile samples.